

Printing date 07/11/2023 Reviewed on 06/20/2023

1 Identification

- · Product identifier
- · Trade name: Glass Sealant
- · Article number: 92341215
- · Application of the substance / the mixture Hydrophobing agent/ water repellent
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Nextzett GmbH

An der Höhe 15

D-51674 Wiehl-Marienhagen

Deutschland

Tel: +49 2261 6095433 Fax: +49 2261 6095429

Email: info@nextzett.de / www.nextzett.de

- · Information department: Chemtel
- · Emergency telephone number: 1-800-255-3924 (USA AND CANADA)

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flammable Liquids 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carcinogenicity 1A H350 May cause cancer.



GHS07

Eye Irritation 2A

H319 Causes serious eye irritation.

Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms







GHS02 GHS07

GHS08

- · Signal word Danger
- Hazard-determining components of labeling:

propan-2-ol

sulphuric acid

· Hazard statements

Highly flammable liquid and vapor.

(Contd. on page 2)



Printing date 07/11/2023 Reviewed on 06/20/2023

Trade name: Glass Sealant

(Contd. of page 1)

Causes serious eye irritation.

May cause cancer.

May cause drowsiness or dizziness.

Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood. Keep

away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment. Use

only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash hands thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear eye protection / face protection.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF

INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use CO2, powder or water spray to extinguish. Store

in a well-ventilated place. Keep container tightly closed. Store in a

well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of the substances listed below with nonhazardous additions.

| l | · Dangerous compo | onents: | |
|---|-------------------|----------------|------------|
| I | CAS: 67-63-0 | propan-2-ol | ≥50-100% |
| ľ | CAS: 7664-93-9 | sulphuric acid | ≥0.1-<2.5% |

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product. ·

After inhalation: Supply fresh air; consult doctor in case of complaints.

- · After skin contact: Immediately rinse with water.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. • After swallowing: If symptoms persist consult doctor.

(Contd. on page 3)



Printing date 07/11/2023 Reviewed on 06/20/2023

Trade name: Glass Sealant

(Contd. of page 2)

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available. Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. • For safety reasons unsuitable extinguishing agents: Water with full jet

- · Special hazards arising from the substance or mixture No further relevant information available. · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures Wear

protective equipment. Keep unprotected persons away.

· Environmental precautions: Do not allow to enter sewers/ surface or ground water. ·

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment. See

Section 13 for disposal information.

· Protective Action Criteria for Chemicals

| · <i>PAC-1</i> : | | |
|------------------|---------------------|------------------------|
| CAS: 67-63-0 | propan-2-ol | 400 ppm |
| CAS: 63148-62-9 | Polydimethylsiloxan | 65 mg/m³ |
| CAS: 7664-93-9 | sulphuric acid | 0.20 mg/m^3 |
| · PAC-2: | 2 | |
| CAS: 67-63-0 | propan-2-ol | 2000* ppm |
| CAS: 63148-62-9 | Polydimethylsiloxan | 720 mg/m³ |
| CAS: 7664-93-9 | sulphuric acid | 8.7 mg/m^3 |
| · PAC-3: | | (8) |
| CAS: 67-63-0 | propan-2-ol | 12000** ppm |
| CAS: 63148-62-9 | Polydimethylsiloxan | $4,300 \text{ mg/m}^3$ |
| CAS: 7664-93-9 | sulphuric acid | 160 mg/m³ |

7 Handling and storage

- · Handling:
- Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

(Contd. on page 4)



Printing date 07/11/2023 Reviewed on 06/20/2023

Trade name: Glass Sealant

(Contd. of page 3)

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

· Conditions for safe storage, including any incompatibilities ·

Storage.

• Requirements to be met by storerooms and receptacles: Store in a cool location.

Information about storage in one common storage facility: Not required.

Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles. ·

Storage class: 3

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

Additional information about design of technical systems: No further data; see section 7.

Control parameters

· Components with limit values that require monitoring at the workplace:

CAS: 67-63-0 propan-2-ol

PEL Long-term value: 980 mg/m³, 400 ppm

REL Short-term value: 1225 mg/m³, 500 ppm

Long-term value: 980 mg/m³, 400 ppm

TLV Short-term value: 400 ppm

Long-term value: 200 ppm

BEI, A4

CAS: 7664-93-9 sulphuric acid

PEL Long-term value: 1 mg/m³

REL Long-term value: 1 mg/m³

TLV Long-term value: 0.2* mg/m³ *as thoracic fraction, A2

· Ingredients with biological limit values:

CAS: 67-63-0 propan-2-ol

BEI 40 mg/L

Medium: urine

Time: end of shift at end of workweek

Parameter: Acetone (background, nonspecific)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

(Contd. on page 5)



Printing date 07/11/2023 Reviewed on 06/20/2023

Trade name: Glass Sealant

(Contd. of page 4)

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



Protective gloves

Suitable chemical resistent protective gloves (EN374) also at prolonged, direct contact (recommended protection index 6, corresponding 480 minutes permeation time according to EN 374) e.g. from Nitrilkautschuk (0,33-0,5 mm) Polyvinylchlorid (1mm).

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· **Body protection:** Protective work clothing

9 Physical and chemical properties

| · Information on basic physical and General Information | nation on basic physical and chemical properties | |
|--|--|--|
| · Appearance: | | |
| Form: | Fluid | |
| Color: | Colorless | |
| · Odor: | Alcohol-like | |
| · Odor threshold: | Not determined. | |
| · pH-value: | Not determined. | |
| · Change in condition | | |
| Melting point/Melting range: | Undetermined. | |
| Boiling point/Boiling range: | 80 °C (176 °F) | |
| · Flash point: | 12 °C (53.6 °F) | |
| · Flammability (solid, gaseous): | Highly flammable. | |
| · Auto igniting: | 425 °C (797 °F) | |

(Contd. on page 6)



Printing date 07/11/2023 Reviewed on 06/20/2023

Trade name: Glass Sealant

| | (Contd. of page |
|---|--|
| Decomposition temperature: | Not determined. |
| · Ignition temperature: | Product is not selfigniting. |
| · Danger of explosion: | Product is not explosive. However, formation of explosive air/vapor mixtures are possible. |
| · Explosion limits: | |
| Lower: | 2 Vol % |
| Upper: | 12 Vol % |
| · Vapor pressure at 20 °C (68 °F): | 43 hPa (32.3 mm Hg) |
| Density at 20 °C (68 °F): | 0.8 g/cm³ (6.676 lbs/gal) |
| · Relative density | Not determined. |
| · Vapor density | Not determined. |
| · Evaporation rate | Not determined. |
| · Solubility in / Miscibility with | |
| Water: | Not miscible or difficult to mix. |
| · Partition coefficient (n-octanol/wate | r): Not determined. |
| · Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic: | Not determined. |
| · Solvent content: | |
| Organic solvents: | 89.0 % |
| VOC content: | 89.00 % |
| | 712.0 g/l / 5.94 lb/gal |
| VOC (EC) | 89.00 % |
| Solids content: | 11.0 % |
| · Other information | No further relevant information available. |

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications. Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

CAS: 67-63-0 propan-2-ol

Oral LD50 5,045 mg/kg (rat)

(Contd. on page 7)



Printing date 07/11/2023 Reviewed on 06/20/2023

Trade name: Glass Sealant

(Contd. of page 6) 12,800 mg/kg (rabbit) LD50 Dermal Inhalative LC50/4 h 30 mg/l (rat)

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: Irritating effect.
- · **Sensitization:** No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

| · Carcinogenic categories | | | | |
|--|---------------------------------------|--|--|--|
| · IARC (International Agency for Research on Cancer) | | | | |
| CAS: 67-63-0 prop | | | | |
| CAS: 7664-93-9 sulp | huric acid 1 | | | |
| · NTP (National Toxicology Program) | | | | |
| CAS: 7664-93-9 sulp | huric acid K | | | |
| · OSHA-Ca (Occupati | ional Safety & Health Administration) | | | |
| None of the ingredients i | is listed. | | | |

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.

Persistence and degradability

The surfactants contained in the product correspond to the legislation on the environmental compatibility of detergents and are biodegradable.

- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.

Mobility in soil No further relevant information available.

- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB**: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 8)



Printing date 07/11/2023 Reviewed on 06/20/2023

Trade name: Glass Sealant

(Contd. of page 7)

- Uncleaned packagings:
 Recommendation: Disposal must be made according to official regulations.

| Transport information | |
|---|---|
| UN-Number | |
| DOT, IMDG, IATA | UN1219 |
| UN proper shipping name | |
| DOT | Isopropanol |
| IMDG, IATA | ISOPROPANOL (ISOPROPYL ALCOHOL) |
| Transport hazard class(es) | |
| DOT | |
| 3 | |
| Class | 3 Flammable liquids |
| Label | 3 |
| IMDG, IATA | |
| Class Label | 3 Flammable liquids 3 |
| Packing group DOT, IMDG, IATA | II |
| Environmental hazards: | Not applicable. |
| Special precautions for user | Warning: Flammable liquids |
| Hazard identification number (Kemler co | |
| EMS Number: | F-E,S-D |
| Stowage Category | В |
| Transport in bulk according to Annex II o MARPOL73/78 and the IBC Code | of Not applicable. |
| Transport/Additional information: | |
| DOT | |
| Quantity limitations | On passenger aircraft/rail: 5 L |
| | On cargo aircraft only: 60 L |
| IMDG | |
| Limited quantities (LQ) | IL |
| Excepted quantities (EQ) | Code: E2 |
| | Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml |



Printing date 07/11/2023 Reviewed on 06/20/2023

Trade name: Glass Sealant

(Contd. of page 8)

· UN "Model Regulation":

UN 1219 ISOPROPANOL (ISOPROPYL ALCOHOL), 3, II

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- Section 355 (extremely hazardous substances):

CAS: 7664-93-9 sulphuric acid

Section 313 (Specific toxic chemical listings):

CAS: 67-63-0

propan-2-ol

CAS: 7664-93-9 sulphuric acid

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Hazardous Air Pollutants

None of the ingredients is listed.

- **Proposition 65**
- · Chemicals known to cause cancer:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for females: None

of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- · Carcinogenic categories
- · EPA (Environmental Protection Agency)

None of the ingredients is listed.

TLV (Threshold Limit Value)

CAS: 67-63-0 propan-2-ol A4

CAS: 7664-93-9 sulphuric acid

A2

· NIOSH-Ca (National Institute for Occupational Safety and Health) None

of the ingredients is listed.

- · National regulations:
- · Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

- · Other regulations, limitations and prohibitive regulations
- Besonders besorgniserregende Stoffe (SVHC) gemäß REACH, Artikel 57 None

of the ingredients is listed.

(Contd. on page 10)



Printing date 07/11/2023 Reviewed on 06/20/2023

Trade name: Glass Sealant

(Contd. of page 9)

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Contact:
- · Date of preparation / last revision 06/20/2023
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 2: Flammable liquids - Category 2

Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A

Carcinogenicity 1A: Carcinogenicity - Category 1A

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) - Category 3 · *

Data compared to the previous version altered.

US