

according to Regulation (EC) No 1907/2006

Tire Foam (Aerosol)

Print date: 08.05.2018 Page 1 of 4

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Tire Foam (Aerosol) Item: 97291015

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Tyre Care

1.3. Details of the supplier of the safety data sheet

Company name: nextzett GmbH Street: An der Höhe 15

Place: D-51674 Wiehl-Marienhagen

Telephone: +49 2261 6095433 Telefax:+49 2261 6095429

e-mail: matthias.gregorzewski@nextzett.de

Contact person: Mr. Gregorzewski Internet: www.nextzett.de Responsible Department: Mr. Gregorzewski

1.4. Emergency telephone CHEMTEL 1-800-255-3924 (USA AND CANADA); +1-813-248-0585 (Worldwide International)

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories: Aerosol: Aerosol 1

Serious eye damage/eye irritation: Eye Dam. 1

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

Causes serious eye irritation.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

Polyoxyethylene (7) Tridecylether **Signal word:**Danger

Pictograms:





Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurized container: May burst if heated.

H319 Causes serious eye irritation.



according to Regulation (EC) No 1907/2006

Tire Foam (Aerosol)

Print date: 08.05.2018 Page 2 of 4

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

SECTION 4: First aid measures

4.1. Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

SECTION 6: Accidental release measures

SECTION 7: Handling and storage

7.1. Precautions for safe handling

7.2. Conditions for safe storage, including any incompatibilities

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.2. Exposure controls

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Aerosol
Colour: whitish
Odour: characteristic

Test method

pH-Value (at 20 °C): 10,3 DIN 19268

Changes in the physical state

Melting point:

Undetermined.

Initial boiling point and boiling range:

-44 °C

Flash point:

-80 °C



according to Regulation (EC) No 1907/2006

Tire Foam (Aerosol)

Print date: 08.05.2018 Page 3 of 4

Lower explosion limits:

Upper explosion limits:

10,9 vol. %

Ignition temperature:

450 °C

Vapour pressure:

4200 hPa

Density:

1 g/cm³

Water solubility:
(at 20 °C)

Viscosity / dynamic:

Undetermined.

Viscosity / kinematic: Undetermined.

9.2. Other information

Solid content: ca. 0,5%

SECTION 10: Stability and reactivity

SECTION 11: Toxicological information

11.1. Information on toxicological effects

SECTION 12: Ecological information

SECTION 13: Disposal considerations

13.1. Waste treatment methods

SECTION 14: Transport information

Marine transport (IMDG)

Marine pollutant: No EmS: F-D, S-U

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

2010/75/EU (VOC): 7,53 % (75,3 g/l)

National regulatory information

Water contaminating class (D): 1 - slightly water contaminating

SECTION 16: Other information



according to Regulation (EC) No 1907/2006

Tire Foam (Aerosol)

Print date: 08.05.2018 Page 4 of 4

Relevant H and EUH statements (number and full text)

H222 Extremely flammable aerosol.

H229 Pressurized container: May burst if heated.

H319 Causes serious eye irritation.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)